

WELLSAN

energy is mandatory

wellpro -T series

10-1000 kVA **3:3**
PHASE

ISOLATION TRANSFORMER BASED

ONLINE UPS



HIGHLIGHTS


- IGBT PWM Rectifier & Inverter Technology
- Low Input Current THD (<3%)
- High Input Power Factor (>0.99)

DSP Power Factor Corrected IGBT Rectifier

- Equipped with its new IGBT rectifier BOXER Series keeps your critical loads protected while its space-saving compact design and front access for maintenance successfully reduce mean time to repair (MTTR).
- Thanks to the wide variety of accessories and options BOXER Series presents maximum flexibility advantage to users and optimizes total cost of ownership.



WWW.WELLSAN-UPS.COM.TR



WELLSAN
energy is mandatory

specification										
Capacity		10kVA	15kVA	20kVA	30kVA	40kVA	60kVA	80kVA	100kVA	120kVA
Power Watt		9kW	13.5kW	18kW	27kW	36kW	54kW	72kW	90kW	108kW
INPUT										
Nominal Voltage		380/400/415 VAC 3 P+N (Optional 220/380 VAC -37% +22% 3 P+N+PE)								
Voltage Tolerance		-20% +15%								
Frequency Tolerance		50 / 60 Hz ±10% (Selectable)								
Power Factor		>0.99								
Total Harmonic Distortion (THDi)		<3%								
OUTPUT										
Power Factor		0.9 (1 Optional)								
Nominal Voltage		380/400/415 VAC 3 P+N								
Voltage Tolerance		Statik ±1, Dynamic ±3								
Frequency Tolerance		50 / 60 Hz ±0,01% (Battery Mode)								
Output THD		Linear Load <1% / Non-Linear Load <3%								
Crest Factor		3:1								
Overload Capacity*		At 125% Load 10min, At 150% Load 1min								
Efficiency (Online Mode)		Up to 92%								
Efficiency (Eco Mode)		Up to 99%								
BYPASS										
Nominal Voltage		380/400/415 VAC 3 P+N								
Voltage Tolerance		%15 (Configurable from 10% to 30%)								
Frequency Tolerance		±5 (Selectable)								
BATTERY										
Type		VRLA / GEL								
Quantity (12V DC VRLA)		30								
Charge Capacity		25% of Active Power (Nominal 0,1 C10, Adjustable)								
Recharge Time		6-8 hours								
Internal Battery		60 x 7Ah or 9Ah				External Battery				
ENVIRONMENTAL										
Operating Temperature		For UPS 0°C/+40°C For Battery +15°C/+25°C								
Storage Temperature		For UPS -15°C/+45°C For Battery 0°C/+30°C								
Protection Class		IP20								
Humidity		0-95% (Without Condensation)								
Altitude		<1000m: Correction Factor 1, <2000m: Correction Factor >0.92, <3000m: Correction Factor >0.84								
Noise Level										
COMMUNICATION										
Communication Port		RS232 Standart, RS485 and SNMP Adapter Option								
STANDARDS										
Quality		ISO 9001, ISO 14001, ISO 45001, ISO 10002, CE, TSE, TSE-HYB								
Performance		EN62040-3 (VFI-SS-111, Bureau Veritas Certified)								
EMC/LVD		EN62040-2, EN62040-1, TS EN ISO/IEC 17025 Acredited Test Report								
DIMENSIONS & WEIGHT		10kVA	15kVA	20kVA	30kVA	40kVA	60kVA	80kVA	100kVA	120kVA
Cabinet Dimensions (mm)	Width	490						530		
	Depth	805						780		
	Height	1190						1290		
Net Weight (kg)		125	126	131	145	173	323	222	231	240
Packaging Dimensions (mm)	Width	600						650		
	Depth	900						900		
	Height	1400						1400		
Gross Weight (kg)		145	146	151	166	193	353	253	261	270

www.wellsan-ups.com.tr



Address :Zafer Mah.Babaocagi SK. NO.2-4 iC kapi NO : 50 Bahcelievler/IST
TURKEY .

sales@wellsan-ups.com.tr .

specification										
Capacity		160kVA	200kVA	250kVA	300kVA	400kVA	500kVA	600kVA	800kVA	1000kVA
Power Watt		144kW	180kW	225kW	270kW	360kW	450kW	540kW	720kW	900kW
INPUT										
Nominal Voltage		380/400/415 VAC 3 P+N (Optional 220/380 VAC -37% +22% 3 P+N+PE)								
Voltage Tolerance		-20% +15%								
Frequency Tolerance		50 / 60 Hz ±10% (Selectable)								
Power Factor		>0.99								
Total Harmonic Distortion (THDi)		<3%								
OUTPUT										
Power Factor		0.9 (1 Optional)								
Nominal Voltage		380/400/415 VAC 3 P+N								
Voltage Tolerance		Statik ±1, Dynamic ±3								
Frequency Tolerance		50 / 60 Hz ±0,01% (Battery Mode)								
Output THD		Linear Load <1% / Non-Linear Load <3%								
Crest Factor		3:1								
Overload Capacity*		At 125% Load 10min, At 150% Load 1min								
Efficiency (Online Mode)		Up to 92%								
Efficiency (Eco Mode)		Up to 99%								
BYPASS										
Nominal Voltage		380/400/415 VAC 3 P+N								
Voltage Tolerance		15% (Configurable from 10% to 30%)								
Frequency Tolerance		±5 (Selectable)								
BATTERY										
Type		VRLA / GEL								
Quantity (12V DC VRLA)		30								
Charge Capacity		25% of Active Power (Nominal 0,1 C10, Adjustable)								
Recharge Time		6-8 hours								
Internal Battery		External Battery								
ENVIRONMENTAL										
Operating Temperature		For UPS 0°C/+40°C For Battery +15°C/+25°C								
Storage Temperature		For UPS -15°C/+45°C For Battery 0°C/+30°C								
Protection Class		IP20								
Humidity		0-95% (Without Condensation)								
Altitude		<1000m: Correction Factor 1, <2000m: Correction Factor >0.92, <3000m: Correction Factor >0.84								
Noise Level		<72dBA					<74dBA			<75dBA
COMMUNICATION										
Communication Port		RS232 Standart, RS485 and SNMP Adapter Option								
STANDARDS										
Quality		ISO 9001, ISO 14001, ISO 45001, ISO 10002, CE, TSE, TSE-HYB								
Performance		EN62040-3 (VFI-SS-111, Bureau Veritas Certified)								
EMC/LVD		EN62040-2, EN62040-1, TS EN ISO/IEC 17025 Acredited Test Report								
DIMENSIONS & WEIGHT		160kVA	200kVA	250kVA	300kVA	400kVA	500kVA	600kVA	800kVA	1000kVA
Cabinet Dimensions (mm)	Width	830			1200			2000		
	Depth	870			825			870		
	Height	1800			1854			2050		
Net Weight (kg)		475	490	553	830	840	850	1510	1740	1740
Packaging Dimensions (mm)	Width	900			1370			2100		
	Depth	970			845			950		
	Height	2040			2040			2250		
Gross Weight (kg)		505	520	583	870	880	890	1590	1820	1820

